



TECHNICAL SPECIFICATIONS					
PRODUCT CHARACTERISTICS					
FILM AUTOMATIC 12 My					
MEDIUM SPRING (Micras)	12				
WIDTH (metres)	0,5				
METRES PER COIL (linear metres)	2569				
COIL WEIGHT (kg)	16	(+/- 1%)			
NET PLASTICO PESO (kg)	14,2	(+/-1%)			
MANDRIL DOG (kg)	1,8	(+/- 4%)			
COUTER COIL OUTER DIAMETER (mm)	240 mm	(+/- 5 mm)			
INSIDE DIAMETER OF SPINDLE (mm)	77 mm (+/- 1 mm)	(+/- 1 mm)			
OUTER DIAMETER OF SPINDLE (mm)	110 mm (+/- 1 mm)	(+/- 1 mm)			
BENEFITS	<p>EXCELLENT THICKNESS AND WINDING UNIFORMITY.</p> <p>GOOD ADHESION, HIGH HOLDING POWER AND LOAD STABILITY. ADHESIVENESS ON THE INNER SIDE. MINIMUM LEVEL OF GELS.</p>				
ORGANOLEPTIC CHARACTERISTICS	ODOUR: NO FOREIGN ODOUR COLOUR: TRANSPARENT				
DESCRIPTION OF THE PROCESS					
TRANSFORMATION SYSTEM	THREE-LAYER CAST CO-EXTRUSION				
MODALITY	MONORIENTED				
PHYSICO-CHEMICAL CHARACTERISTICS OF THE RAW MATERIAL					
PHYSIO-MECHANICAL PROPERTIES	Standard	Unit of Measure	Value Logitudinal	Value Transversal	Tolerance
THICKNESS	ASTM D374	mm	12	12	-2/+2mm
TENSION LOSS OF ELASTICITY	ASTM D 882-10	N/ mm2	8.3	8.3	+/-5 %
BREAKING STRAIN	ASTM D 882-10	N/ mm2	27.0	19.0	+/-10 %
ELASTIC MODULUS	ASTM D882-10	N/ mm2	80	90	+/-10 %
IMPACT RESISTANCE	ASTM D 1709-91	g	140		+/-10 %
PRE-ESTABLISHED GUARANTEED	Europack method	%	300	-----	

ADHESIVITY	Europack method	%	5	ELASTOMERO	
PALLETISING CONDITIONS					
<ul style="list-style-type: none"> > REELS APPROX. 16 KGS > > PALLETTE MODEL CP6, MEDIDAS 1,000 x 1,200 mm > > PALLETISED: 3 PLANTAS DE 23 BOBINAS > > TOTAL PALLET WEIGHT 1120 Kg. APROX. > > PALLET HEIGHT 175 mm APROX. > > LAYING OF CARDBOARD SHEETING ON THE BASE AND ON THE TWO FLOORS. > > THE PRODUCT DOES NOT PROTRUDE FROM THE PALLET. > FOR GOOD LOAD STABILITY THE PALLETS ARE STRETCH WRAPPED WITH HIGH QUALITY STRETCH FILM. 					
HYGIENE AND SAFETY					
<ul style="list-style-type: none"> > THESE PRODUCTS ARE NON-HAZARDOUS AND NON-TOXIC. BEHAVIOUR IS STABLE UNDER NORMAL CONDITIONS OF USE HANDLING AND STORAGE. > NO ADDITIVES BASED ON HEAVY METALS ARE USED IN ITS MANUFACTURE. > THE PRODUCT IS 100% RECYCLABLE. 					